

TW65

# TAKEUCHI<sup>®</sup>

*The Power of Product and Support*



*All Takeuchi wheel loaders share our commitment to the highest standards in quality and performance. They are engineered to be durable and powerful while providing mobility and stability. The specifications and features make the TW65 reliable to own, comfortable to operate and a performance leader on the job.*

*When you invest in a Takeuchi, you receive over five decades of equipment innovation, the quality assurance of ISO-9001 certification and responsive after sales support from an industry leader.*

*Try a Takeuchi and feel the power.*

## TW65 Wheel Loader

# TW65 Wheel Loader

- Spacious and comfortable operator's compartment allows for productive and fatigue-free operation

- Hydrostatic drive system with outboard planetary final drives provides durable and efficient power transfer

- Momentary pushbutton control of 100% front and rear axle differential lock provides additional traction in harsh terrain

- Frame oscillation and articulation enhances mobility, stability and operator comfort

- Forward, neutral and reverse functions controlled on-the-go with electrohydraulic thumb switches

## DIMENSIONS AND WEIGHT

Operating Weight (lbs).....	10,362
Overall Width Without Bucket.....	73.6"
Overall Height (Cab).....	104.3"
Overall Length With Bucket.....	205.9"
Maximum Lift Height to Bucket Pin.....	124.8"
Dump Height Fully Raised.....	98.4"
Max. Dump Angle Fully Raised.....	45°
Max. Bucket Rollback at Ground Level.....	48°
Reach Fully Raised.....	24.6"

## PERFORMANCE

Tipping Load, Straight (lbs).....	8,073
Tipping Load, Full Turn (lbs).....	7,143
Operating Capacity (lbs)	
50% of Full Turn Tipping Load.....	3,572
Breakout Force (lbs) Bucket Cylinders.....	11,600
Lift Capacity at Ground Level (lbs).....	10,319
WITH PALLET FORKS	
Static Tipping Load,	
Straight and Articulated (lbs).....	5,600
Lifting Capacity (lbs/ft).....	6,396
Payload 80% Even Surface (lbs).....	4,480
Payload 60% Uneven Surface (lbs).....	3,353
CYCLE TIME	
Raise-Full Load (seconds).....	5.5
Lower-No load (seconds).....	3.5
Dump-Full Load (seconds).....	1.7

## HYDRAULIC SYSTEM

Hydraulic Reservoir Capacity (gal).....	13.7
Auxiliary Hydraulic Flow (gpm).....	15.3
System Operating Pressure (psi).....	3,336

## ENGINE

Make/Model.....	Deutz F4L 2011
Horsepower/RPM (SAE gross).....	59 / 2,300
Maximum Torque (ft-lb/rpm).....	140 / 1,700
Cylinders/CID.....	4 / 189.8
Engine Lubrication (qt).....	11.1
Fuel Tank Capacity (gal).....	26.4
Fuel Consumption (65% of full load) gal/hr.....	2.08
Electrical System (volt/amp).....	12 / 60

## UNDERCARRIAGE

Transmission Type.....	Hydrostatic
Axle Type.....	Planetary Rigid Axles
Parking/Service Brake	
...Spring Applied Hydraulically Released Wet Disc	
Tires.....	405/70R20
Tread Width.....	59.4"
Wheelbase.....	78.7"
Articulation.....	40° / 40°
Oscillation.....	+ or - 12°
Travel Speed (mph).....	12.4
Ground Clearance.....	17.7"

## OPTIONAL BUCKETS

	General Purpose	Construction
Width.....	71.0"	77.0"
Capacity SAE Heaped (cu yd)		
.....	1.11	1.05

## STANDARD FEATURES

- Low and high range travel speed
- Sound absorbing ROPS/FOPS cab with heat
- Operator's compartment entry and exit grab handles and steps
- Dual element air cleaner with restriction indicator
- Front and rear work lights
- Automatic fuel bleed system
- Hydraulic quick attach
- Bucket float function
- Six-way adjustable suspension seat with retractable seat belt
- Two cab mounted rear view mirrors
- Back-up alarm
- Horn
- Vandalism protected lockable engine compartment
- Lift arm safety stop
- Adjustable arm rests
- Auxiliary hydraulic lines conveniently plumbed to bottom of loader arms
- 100% hydraulic inching pedal
- Sun visor, ceiling lamp, coat hook and storage compartment
- Windshield and rear window wiper and wash unit
- Adjustable steering column
- Rear window defrost
- Rear tires follow the same track as front tires
- Z-pattern lift kinematics
- Automatic bucket positioning